



Republic of the Philippines
Office of the President
National Security Council

SUPPLEMENTAL BID BULLETIN NO. 2021-01
15 March 2021

**Supply and Delivery of three (3) units brand new Motor Vehicles
for the National Security Council**

This Supplemental Bid Bulletin No. 2021-01 is issued to amend and clarify the items in the Bidding Documents and the Terms of Reference (TOR). This shall form an integral part of the Bid Documents.

1. All Technical Questions relative to the procurement have been answered during the Pre-Bid Conference. For other technical queries, please refer to the amendment stipulated in this Bid bulletin.
2. There will be no **Warranty Retention** to be imposed for the winning bidder.
3. The bidders can participate and submit bidding proposals in **any of the two (2) lots**.
4. All bidders must comply strictly with the technical specifications base on the Supplemental Bid Bulletin.

REFERENCE	AMENDMENT/ CHANGE / MODIFICATION (In Bold Letters)																																																																																																			
<p>Terms of Reference: II. Scope of Work- A. One (1) unit Brand new Utility Van with the amount of TWO MILLION ONE HUNDRED FORTY-FIVE THOUSAND PESOS ONLY (PhP2,145,000.00)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">QTY</th> <th style="width: 40%;">PARTICULAS</th> <th style="width: 50%;">DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1 unit</td> <td>Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread Grand clearance Fuel tank capacity Seating capacity</td> <td>Minimum: 5265x1950x1990 (mm) 3210 1675x1670 175 70 12</td> </tr> <tr> <td></td> <td>Engine:</td> <td></td> </tr> <tr> <td></td> <td>a. Engine Technology</td> <td>4 cylinders, in line type (cc)</td> </tr> <tr> <td></td> <td>b. Type</td> <td>16 valve DOHC</td> </tr> <tr> <td></td> <td>c. Displacement</td> <td>2755cc</td> </tr> <tr> <td></td> <td>d. Minimum Output</td> <td>176/3400 (ps/Rpm)</td> </tr> <tr> <td></td> <td>e. Maximum Torque</td> <td>450/1600-2400 (Nm/Rpm)</td> </tr> <tr> <td></td> <td>Transmission</td> <td>6-speed automatic</td> </tr> <tr> <td></td> <td>Steering</td> <td>Variable power steering</td> </tr> <tr> <td></td> <td>Wheel/Rim make /Size</td> <td>235x65 R16 Alloy wheel</td> </tr> <tr> <td></td> <td>Airconditioning System</td> <td>Dual manual controls with rear individual vents</td> </tr> <tr> <td></td> <td>Color</td> <td>White or Silver</td> </tr> <tr> <td></td> <td>Free Items</td> <td>Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats</td> </tr> <tr> <td></td> <td>Availability of Spare Parts</td> <td>Readily available from services center nationwide</td> </tr> <tr> <td></td> <td>Warranty</td> <td>3 years or 100,000 kms whichever comes first on the main assembles of engine, transmission differential</td> </tr> </tbody> </table>	QTY	PARTICULAS	DESCRIPTION	1 unit	Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread Grand clearance Fuel tank capacity Seating capacity	Minimum: 5265x1950x1990 (mm) 3210 1675x1670 175 70 12		Engine:			a. Engine Technology	4 cylinders, in line type (cc)		b. Type	16 valve DOHC		c. Displacement	2755cc		d. Minimum Output	176/3400 (ps/Rpm)		e. Maximum Torque	450/1600-2400 (Nm/Rpm)		Transmission	6-speed automatic		Steering	Variable power steering		Wheel/Rim make /Size	235x65 R16 Alloy wheel		Airconditioning System	Dual manual controls with rear individual vents		Color	White or Silver		Free Items	Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats		Availability of Spare Parts	Readily available from services center nationwide		Warranty	3 years or 100,000 kms whichever comes first on the main assembles of engine, transmission differential	<p>Terms of Reference: II. Scope of Work- A. One (1) unit Brand new Utility Van with the amount of TWO MILLION ONE HUNDRED FORTY-FIVE THOUSAND PESOS ONLY (PhP2,145,000.00)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">QTY</th> <th style="width: 40%;">PARTICULAS</th> <th style="width: 50%;">DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1 unit</td> <td>Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread Grand clearance Fuel tank capacity Seating capacity</td> <td>Minimum: 5265x1950x1990 (mm) 3210 1675x1670 175 70 12</td> </tr> <tr> <td></td> <td>Engine:</td> <td></td> </tr> <tr> <td></td> <td>a. Engine Technology</td> <td>4 cylinders, in line type (cc)</td> </tr> <tr> <td></td> <td>b. Type</td> <td>16 valve DOHC</td> </tr> <tr> <td></td> <td>c. Displacement</td> <td>2755cc</td> </tr> <tr> <td></td> <td>d. Minimum Output</td> <td>176/3400 (ps/Rpm)</td> </tr> <tr> <td></td> <td>e. Maximum Torque</td> <td>450/1600-2400 (Nm/Rpm)</td> </tr> <tr> <td></td> <td>Transmission</td> <td>5-speed automatic</td> </tr> <tr> <td></td> <td>Steering</td> <td>Variable power steering</td> </tr> <tr> <td></td> <td>Wheel/Rim make /Size</td> <td>235x65 R16 Alloy wheel</td> </tr> <tr> <td></td> <td>Airconditioning System</td> <td>Dual manual controls with rear individual vents</td> </tr> <tr> <td></td> <td>Color</td> <td>White or Silver</td> </tr> <tr> <td></td> <td>Original Equipment Manufacturing (OEM)</td> <td>Car Stereo (AM/FM)</td> </tr> <tr> <td></td> <td>Free Items</td> <td>Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats</td> </tr> <tr> <td></td> <td>Availability of Spare Parts</td> <td>Readily available from services center nationwide</td> </tr> <tr> <td></td> <td>Warranty</td> <td>3 years or 100,000 kms whichever comes first on the main assembles of engine, transmission differential</td> </tr> </tbody> </table>	QTY	PARTICULAS	DESCRIPTION	1 unit	Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread Grand clearance Fuel tank capacity Seating capacity	Minimum: 5265x1950x1990 (mm) 3210 1675x1670 175 70 12		Engine:			a. Engine Technology	4 cylinders, in line type (cc)		b. Type	16 valve DOHC		c. Displacement	2755cc		d. Minimum Output	176/3400 (ps/Rpm)		e. Maximum Torque	450/1600-2400 (Nm/Rpm)		Transmission	5-speed automatic		Steering	Variable power steering		Wheel/Rim make /Size	235x65 R16 Alloy wheel		Airconditioning System	Dual manual controls with rear individual vents		Color	White or Silver		Original Equipment Manufacturing (OEM)	Car Stereo (AM/FM)		Free Items	Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats		Availability of Spare Parts	Readily available from services center nationwide		Warranty	3 years or 100,000 kms whichever comes first on the main assembles of engine, transmission differential
QTY	PARTICULAS	DESCRIPTION																																																																																																		
1 unit	Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread Grand clearance Fuel tank capacity Seating capacity	Minimum: 5265x1950x1990 (mm) 3210 1675x1670 175 70 12																																																																																																		
	Engine:																																																																																																			
	a. Engine Technology	4 cylinders, in line type (cc)																																																																																																		
	b. Type	16 valve DOHC																																																																																																		
	c. Displacement	2755cc																																																																																																		
	d. Minimum Output	176/3400 (ps/Rpm)																																																																																																		
	e. Maximum Torque	450/1600-2400 (Nm/Rpm)																																																																																																		
	Transmission	6-speed automatic																																																																																																		
	Steering	Variable power steering																																																																																																		
	Wheel/Rim make /Size	235x65 R16 Alloy wheel																																																																																																		
	Airconditioning System	Dual manual controls with rear individual vents																																																																																																		
	Color	White or Silver																																																																																																		
	Free Items	Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats																																																																																																		
	Availability of Spare Parts	Readily available from services center nationwide																																																																																																		
	Warranty	3 years or 100,000 kms whichever comes first on the main assembles of engine, transmission differential																																																																																																		
QTY	PARTICULAS	DESCRIPTION																																																																																																		
1 unit	Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread Grand clearance Fuel tank capacity Seating capacity	Minimum: 5265x1950x1990 (mm) 3210 1675x1670 175 70 12																																																																																																		
	Engine:																																																																																																			
	a. Engine Technology	4 cylinders, in line type (cc)																																																																																																		
	b. Type	16 valve DOHC																																																																																																		
	c. Displacement	2755cc																																																																																																		
	d. Minimum Output	176/3400 (ps/Rpm)																																																																																																		
	e. Maximum Torque	450/1600-2400 (Nm/Rpm)																																																																																																		
	Transmission	5-speed automatic																																																																																																		
	Steering	Variable power steering																																																																																																		
	Wheel/Rim make /Size	235x65 R16 Alloy wheel																																																																																																		
	Airconditioning System	Dual manual controls with rear individual vents																																																																																																		
	Color	White or Silver																																																																																																		
	Original Equipment Manufacturing (OEM)	Car Stereo (AM/FM)																																																																																																		
	Free Items	Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats																																																																																																		
	Availability of Spare Parts	Readily available from services center nationwide																																																																																																		
	Warranty	3 years or 100,000 kms whichever comes first on the main assembles of engine, transmission differential																																																																																																		



Republic of the Philippines
Office of the President
National Security Council

Terms of Reference:

II. Scope of Work-

B. Two (2) units Asian Utility Vehicle (AUV) with the total amount of ONE MILLION EIGHT HUNDRED FORTY THOUSAND PESOS (PhP1,840,000.00)

QTY	PARTICULAS	DESCRIPTION
2	Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread No. of Doors Fuel tank capacity (liters) Seating capacity	Minimum: 5265x1950x1990 (mm). 2655 1425x1435 5 45 5
	Engine Details: a. Engine b. No. of Cylinders c. Valves Per Cylinder d. Valve Configuration e. Fuel System f. Compression Ratio	1.3L Gasoline Engine, In-Line 4 Cylinder 16 Valve DOHC 4 4 DOHC EFI 11.5:1
	Transmission	MT/AT 5-speed
	Performance: Engine Displacement Torque Fuel Type	1329cc 121 Nm Gasoline
	Suspension & Brakes: Front Suspension Rear Suspension	MacPherson Strut Multi-Link
	Wheel/Rim make /Size	185/70 R14 Alloy wheel
	Steering	Electric Power/ tilt/ Rack & Pinion 4.7 turning radius and adjustable Steering Column
	Airconditioning System	Dual manual controls with rear individual vents
	Color	White or Silver
	Free Items	Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats
	Availability of Spare Parts	Readily available from service centers nationwide
	Warranty	3 years or 100,000 kms whichever comes first on the main assemblies of engine, transmission differential

Terms of Reference

VII. Payment Scheme

The NSC shall pay the winning bidder 50% of the amount of contract upon delivery of the vehicles and issuance by NSC of the Inspection and Acceptance Report. The remaining 50% shall be paid upon submission of LTO Official Receipt and Certificate of Registration.

Terms of Reference:

II. Scope of Work-

B. Two (2) units Asian Utility Vehicle (AUV) with the total amount of ONE MILLION EIGHT HUNDRED FORTY THOUSAND PESOS (PhP1,840,000.00)

QTY	PARTICULAS	DESCRIPTION
2	Body Dimension (mm): Overall Length (LxWxH) Wheel base Tread No. of Doors Fuel tank capacity (liters) Seating capacity	Minimum: 4190x1660x1695 (mm) 2655 1425x1435 5 45 5
	Engine Details: a. Engine b. No. of Cylinders c. Valves Per Cylinder d. Valve Configuration e. Fuel System	1.3L Gasoline Engine, In-Line 4 Cylinder 16 Valve DOHC 4 4 DOHC EFI
	Transmission	A/T 4-speed
	Performance: Engine Displacement Torque Fuel Type	1300cc 121 Nm Gasoline
	Suspension & Brakes: Front Suspension Rear Suspension	MacPherson Strut Multi-Link
	Wheel/Rim make /Size	185/70 R14 Alloy wheel
	Steering	Electric Power/ tilt/ Rack & Pinion and adjustable Steering Column
	Airconditioning System	Dual manual controls with rear individual vents
	Color	White or Silver
	Original Equipment Manufacturing (OEM)	Car Stereo (AM/FM)
	Free Items	Standard tools, spare tire with rim, early warning device, seat cover, tint and floor mats
	Availability of Spare Parts	Readily available from service centers nationwide
	Warranty	3 years or 100,000 kms whichever comes first on the main assemblies of engine, transmission differential

Terms of Reference

VII. Payment Scheme

The NSC shall pay the full amount of the contract upon delivery of the vehicles, issuance of the NSC Inspection and Acceptance Report and receipt of the LTO Official Receipt (OR) and Certificate of Registration (CR).

For guidance and information of all concerned.

Filonila D. Balitaan

FILONILA D. BALITAAN
Assistant Director General, GASO
Chairman, Bids & Awards Committee